

## Modular Cooking Range Line 900XP 2-Hot Plates Electric Boiling Top

| ITEM #  |  |
|---------|--|
| MODEL # |  |
| NAME #  |  |
| SIS #   |  |
| AIA#    |  |
| AIA "   |  |



391039 (E9ECED2Q00)

2-hot square plates (4 kW each) electric boiling top

391165 (E9ECED2Q0N)

2-hot plate (4 kW each) electric boiling top

## **Short Form Specification**

### Item No.

To be installed on open base installations, bridging supports or cantilever systems. Two 4 kW square cast-iron hot plates hermetically sealed to the one-piece top. Exterior panels of unit in stainless steel with Scotch Brite finish. Extra strength work top in heavy duty 2 mm stainless steel. Rightangled side edges to allow flush-fitting junction between units

#### Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The two 4kW cast-iron plates are hermtically sealed to the one-piece top. Hot plates with a power of 4kW for each plate.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Top configuration allows installation on ambient base only (not possible to install on refrigerated nor freezer base).
- Suitable for countertop installation.

### Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

APPROVAL:





# Modular Cooking Range Line 900XP 2-Hot Plates Electric Boiling Top


# **Optional Accessories**


| •   |            |  |
|---|------------|--|
| <ul> <li>Pair of cast iron plate bars for electric cooking top</li> </ul> | PNC 206056 |  |
| Junction sealing kit  | PNC 206086 |  |
| Support for bridge type installation,<br>800mm                            | PNC 206137 |  |
| • Support for bridge type installation, 1000mm                            | PNC 206138 |  |
| <ul> <li>Support for bridge type installation,<br/>1200mm</li> </ul>      | PNC 206139 |  |
| <ul> <li>Support for bridge type installation,<br/>1400mm</li> </ul>      | PNC 206140 |  |
| <ul> <li>Support for bridge type installation,<br/>1600mm</li> </ul>      | PNC 206141 |  |
| <ul> <li>Support for bridge type installation,<br/>400mm</li> </ul>       | PNC 206154 |  |
| Water column with swivel arm (water<br>column extension not included)     | PNC 206289 |  |
| <ul> <li>Water column extension for 900 line</li> </ul>                   | PNC 206290 |  |
| Chimney upstand, 400mm  | PNC 206303 |  |
| • - NOTTRANSLATED -   | PNC 206308 |  |
| • - NOTTRANSLATED -   | PNC 206309 |  |
| • Chimney grid net, 400mm (700XP/900)                                     | PNC 206400 |  |
| Side handrail-right/left hand (900XP)                                     | PNC 216044 |  |
| Frontal handrail, 400mm   | PNC 216046 |  |
| Frontal handrail, 800mm   | PNC 216047 |  |
| Frontal handrail, 1200mm  | PNC 216049 |  |
| Frontal handrail, 1600mm  | PNC 216050 |  |
| <ul> <li>Large handrail - portioning shelf,<br/>400mm</li> </ul>          | PNC 216185 |  |
| • Large handrail - portioning shelf,<br>800mm                             | PNC 216186 |  |
| <ul> <li>2 side covering panels for top appliances</li> </ul>             | PNC 216278 |  |
|   |            |  |






# Modular Cooking Range Line 900XP 2-Hot Plates Electric Boiling Top





El = Electrical inlet (power)
EQ = Equipotential screw



## **Electric**

Supply voltage:

380-400 V/3N ph/50-60 Hz

391039 (E9ECED2Q00) 391165 (E9ECED2Q0N)

230 V/3 ph/50/60 Hz

Total Watts: 8 kW

## **Key Information:**

| ncy information.         |          |
|--------------------------|----------|
| Net weight:              | 35 kg    |
| Shipping weight:         | 43 kg    |
| Shipping height:         |          |
| 391039 (E9ECED2Q00)      | 520 mm   |
| 391165 (E9ECED2Q0N)      | 540 mm   |
| Shipping width:          | 460 mm   |
| Shipping depth:          | 1020 mm  |
| Shipping volume:         |          |
| 391039 (E9ECED2Q00)      | 0.24 m³  |
| 391165 (E9ECED2Q0N)      | 0.25 m³  |
| [NOT TRANSLATED]         |          |
| 391039 (E9ECED2Q00)      | EH927    |
| 391165 (E9ECED2Q0N)      | N9CE1    |
| Front Plates Power:      | 4 - 0 kW |
| Back Plates Power:       | 4 - kW   |
| Front Plates dimensions: | 300x300  |
| Back Plates dimensions:  | 300x300  |
|                          |          |

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

