



**Electrolux**  
PROFESSIONAL

## Modular Cooking Range Line 900XP Electric Induction Wok - 400 mm

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



391353 (E9INEDW00P)

Electric single Induction Wok  
(5 kW)

### Short Form Specification

#### Item No. \_\_\_\_\_

Heavy duty glass ceramic wok bowl powered by a 5 kW inductor with overheating safety device. Induction top to maximize heat transfer to the food and reduce energy consumption in stand-by mode. Unit features Pan Detection system: inductor is activated only when an induction-friendly wok pan is placed on the bowl. Side and rear panels of unit entirely in AISI 304 stainless steel with Scotch Brite finish. Extra strength work top in heavy duty 2 mm AISI 304 stainless steel. Right-angled side edges to allow flush-fitting junction between units.

### Main Features

- Heavy duty glass-ceramic wok bowl
- 5kW inductor endowed with overheating safety device.
- Reduced heat emission in the work environment.
- Pan detection system - the inductor is switched on only when an induction-friendly wok pan is placed on the bowl.
- IPX5 water protection.
- Pots diameter to be used : min 12cm, max 28 cm in order to obtain maximum heating efficiency.
- Suitable for countertop installation.

### Construction

- Side and rear panel in AISI304 stainless steel.
- All the functional components are accessible via the front of the appliance.
- Unit is 930 mm deep to give a larger working surface area.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- All exterior panels in Stainless Steel with Scotch Brite finishing.

### Sustainability



- High efficiency (up to 90%) induction heating system maximizes the heat transferred to the food and reduces energy consumption in stand-by mode.
- [NOT TRANSLATED]

### Optional Accessories


- |   |                                     |
|---|-------------------------------------|
| • Junction sealing kit  | PNC 206086 <input type="checkbox"/> |
| • Support for bridge type installation, 800mm                 | PNC 206137 <input type="checkbox"/> |
| • Support for bridge type installation, 1000mm                | PNC 206138 <input type="checkbox"/> |
| • Support for bridge type installation, 1200mm                | PNC 206139 <input type="checkbox"/> |
| • Support for bridge type installation, 1400mm                | PNC 206140 <input type="checkbox"/> |
| • Support for bridge type installation, 1600mm                | PNC 206141 <input type="checkbox"/> |
| • Support for bridge type installation, 400mm                 | PNC 206154 <input type="checkbox"/> |
| • Induction Wok pan with wooden handle (diam. 360mm)          | PNC 910613 <input type="checkbox"/> |
| • Induction Wok pan with stainless steel handle (diam. 360mm) | PNC 911587 <input type="checkbox"/> |
| • Stainless steel lid for Wok pan diam. 360mm                 | PNC 911588 <input type="checkbox"/> |

APPROVAL: \_\_\_\_\_




Experience the Excellence  
[www.electroluxprofessional.com](http://www.electroluxprofessional.com)  
[professional@electrolux.com](mailto:professional@electrolux.com)

Front




Side



EI = Electrical inlet (power)  
 EQ = Equipotential screw

Top



### Electric

Supply voltage:	380-400 V/3 ph/50/60 Hz
Total Watts:	5 kW
Predisposed for:	380-400V 3~ 50/60Hz 5kW

### Key Information:

Induction compatible pots & pans must be used.

External dimensions, Width:	400 mm
External dimensions, Depth:	930 mm
External dimensions, Height:	250 mm
Net weight:	30 kg
[NOT TRANSLATED]	N9CIN
Back Plates dimensions:	Ø 300
Induction Top Dimensions (width):	400 mm
Induction Top Dimensions (depth):	930 mm