

## SkyLine ProS Electric Combi Oven 6GN1/1

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	
AIA "	_



227600 (ECOE61K2S0)

SkyLine ProS combi boilerless oven with touch screen control, 6x1/1GN, electric, 2 cooking modes (recipe program, manual), automatic cleaning

#### **Short Form Specification**

#### Item No.

Combi oven with high resolution full touch screen interface, multilanguage.

- Boilerless steaming function to add and retain moisture.
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels.
- SkyClean: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid.
- Cooking modes: Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); EcoDelta cooking cycle.
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, automatic backup mode to avoid downtime.
- USB port to download HACCP data, programs and settings. Connectivity ready.
- Single sensor core temperature probe.
- Double-glass door with LED lights.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

#### **Main Features**

- Boilerless steaming function to add and retain moisture for high quality, consistent cooking results.
- Dry hot convection cycle (max 300 °C) ideal for low humidity cooking. Automatic moistener (11 settings) for boiler-less steam generation.
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 20 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Single sensor core temperature probe included.
- Pictures upload for full customization of cooking cycles.
- Automatic fast cool down and pre-heat function.
- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).
- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 6 GN 1/1 trays.
- [NOT TRANSLATED]

#### Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX 5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

#### User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) color-blind friendly panel.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- USB port to download HACCP data, share cooking







## SkyLine ProS Electric Combi Oven 6GN1/1

PNC 922362

PNC 922382

PNC 922386

PNC 922390

PNC 922600

PNC 922606

PNC 922607

PNC 922610

PNC 922612

PNC 922614

PNC 922615

• Grid for whole duck (8 per grid - 1,8kg

• Wall mounted detergent tank holder

• Tray rack with wheels, 6 GN 1/1, 65mm

Tray rack with wheels, 5 GN 1/1, 80mm

Bakery/pastry tray rack with wheels

400x600mm for 6 GN 1/1 oven and

blast chiller freezer, 80mm pitch (5

• Slide-in rack with handle for 6 & 10 GN

• Open base with tray support for 6 & 10

• Cupboard base with tray support for 6

Hot cupboard base with tray support

for 6 & 10 GN 1/1 oven holding GN 1/1

• Tray support for 6 & 10 GN 1/1

disassembled open base

• USB single point probe

each), GN 1/1

pitch

pitch

runners)

1/1 oven

GN 1/1 oven

& 10 GN 1/1 oven

or400x600mm

programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).

- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.

#### Sustainability



- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler (Registered Design at EPO).
- Reduced powerfunction for customized slow cooking cycles.
- SkyClean: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinseonly) and green functions to save energy, water, detergent and rinse aid. Also programmable with delayed start.
- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.

				_
Optional Accessories			<ul> <li>External connection kit for liquid PNC 922618 detergent and rinse aid</li> </ul>	
•	PNC 922003		• Grease collection kit for GN 1/1-2/1 PNC 922619	
GN ovens	FINC 922003	_	cupboard base (trolley with 2 tanks,	
Pair of 1/1 GN AISI 304 grids	PNC 922017		open/close device for drain)	_
• Couple of grids for whole chicken 1/1GN			<ul> <li>Stacking kit for 6+6 GN 1/1 ovens on electric 6+10 GN 1/1 GN ovens</li> </ul> PNC 922620	
(8 per grid) • ONE 1/1GN AISI 304 GRID FOR AOS	PNC 922062		• Trolley for slide-in rack for 6 & 10 GN 1/1 PNC 922626	
OVEN USA	FINC 722002	_	oven and blast chiller freezer	
<ul> <li>Grid for whole chicken 1/2GN (4 per</li> </ul>	PNC 922086		<ul> <li>Trolley for mobile rack for 2 stacked 6 PNC 922628 GN 1/1 ovens on riser</li> </ul>	
grid - 1,2kg each)			• Trolley for mobile rack for 6 GN 1/1 on 6 PNC 922630	
Side external spray unit (needs to be	PNC 922171		or 10 GN 1/1 ovens	_
mounted outside and includes support for mounting to oven)			• Riser on feet for 2 6 GN 1/1 ovens or a 6 PNC 922632	
<ul> <li>Baking tray with 5 rows (baguette),</li> </ul>	PNC 922189		GN 1/1 oven on base	
perforated aluminium with silicon	1110 /2210/	_	• Riser on wheels for stacked 2x6 GN 1/1 PNC 922635	
coating (400x600x38)			ovens, height 250mm	
<ul> <li>Baking tray with 4 edges, perforated aluminium (400x600x20)</li> </ul>	PNC 922190		<ul> <li>Stainless steel drain kit for 6 &amp; 10 GN PNC 922636 oven, dia=50mm</li> </ul>	
Baking tray with 4 edges, aluminium	PNC 922191		• Plastic drain kit for 6 &10 GN oven, PNC 922637	
(400x600x20)			dia=50mm	
<ul> <li>2 frying baskets for ovens</li> </ul>	PNC 922239		Trolley with 2 tanks for grease PNC 922638 collection	
<ul> <li>Pastry grid, 400x600mm, AISI 304</li> </ul>	PNC 922264		Grease collection kit for open base (2 PNC 922639	
stainless steel			tanks, open/close device and drain)	_
Double-click closing catch for door	PNC 922265		• Wall support for 6 GN 1/1 oven PNC 922643	
• Grid for whole chicken 1/1GN (8 per grid	PNC 922266		• Dehydration tray, GN 1/1, H=20mm PNC 922651	
<ul><li>1,2kg each)</li><li>USB probe for Sous-Vide cooking -</li></ul>	PNC 922281		• Flat dehydration tray, GN 1/1 PNC 922652	
available on Touchline ovens with	PNC 922201	ч	• Open base for 6 & 10 GN 1/1 oven, PNC 922653	
software versions after 4.10			disassembled - NO accessory can be	
<ul> <li>Fat collection tray 100 mm</li> </ul>	PNC 922321		fitted with the exception of 922382	_
Kit universal skewer rack and 4 long	PNC 922324		<ul> <li>Bakery/pastry rack kit for 6 GN 1/1 oven PNC 922655 with 5 racks 400x600mm and 80mm</li> </ul>	
skewers for Lenghtwise ovens			pitch	
<ul> <li>Universal skewer rack</li> </ul>	PNC 922326		• Stacking kit for gas 6 & 10 GN 1/1 oven PNC 922657	
<ul> <li>4 long skewers</li> </ul>	PNC 922327		placed on 7kg and 15kg crosswise blast	_
<ul> <li>Smoker for lengthwise and crosswise</li> </ul>	PNC 922338		chiller freezer	
ovens - 4 kinds of smoker wood chips are available on request			Heat shield for stacked ovens 6 GN 1/1 PNC 922660	
<ul><li>Multipurpose hook</li></ul>	PNC 922348		on 6 GN 1/1	
4 flanged feet for 6 & 10 GN , 2",	PNC 922351		<ul> <li>Heat shield for stacked ovens 6 GN 1/1 PNC 922661 on 10 GN 1/1</li> </ul>	
100-130mm	1110 /22001	_	on to ore in	















### SkyLine ProS Electric Combi Oven 6GN1/1

	Heat shield for 6 GN 1/1 oven Compatibility kit for installation of 6 GN 1/1 electric oven on previous 6 GN 1/1 electric oven (old stacking kit 922319 is also needed)	PNC 922662 PNC 922679	
•	Fixed tray rack for 6 GN 1/1 and 400x600mm grids	PNC 922684	
	Kit to fix oven to the wall Tray support for 6 & 10 GN 1/1 oven base	PNC 922687 PNC 922690	
•	4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm	PNC 922693	
	Detergent tank holder for open base Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base	PNC 922699 PNC 922702	
•	Wheels for stacked ovens	PNC 922704	
	Mesh grilling grid, GN 1/1	PNC 922713	
•	Probe holder for liquids	PNC 922714	
	Odour reduction hood with fan for 6 & 10 GN 1/1 electric ovens	PNC 922718	
	Condensation hood with fan for 6 & 10 GN 1/1 electric oven	PNC 922723	
•	Exhaust hood with fan for 6 & 10 GN 1/1 ovens	PNC 922728	
	Exhaust hood without fan for 6&10 1/1GN ovens	PNC 922733	
	Fixed tray rack, 5 GN 1/1, 85mm pitch	PNC 922740	
	4 high adjustable feet for 6 & 10 GN ovens, 230-290mm	PNC 922745	
	Tray for traditional static cooking, H=100mm	PNC 922746	
•	Double-face griddle, one side ribbed and one side smooth, 400x600mm	PNC 922747	
	Trolley for grease collection kit	PNC 922752	
	Water inlet pressure reducer	PNC 922773	
•	Kit for installation of electric power peak management system for 6 & 10 GN Oven	PNC 922774	
•	Extension for condensation tube, 37cm	PNC 922776	
	Non-stick universal pan 1/1GN H=20mm		
	Non-stick universal pan 1/1GN H=40mm		
	Non-stick universal pan 1/1GN H=60mm	PNC 925002	
	Frying griddle GN 1/1 for ovens	PNC 925003	
	Aluminium oven grill GN 1/1	PNC 925004	
	Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1	PNC 925005	
•	Flat baking tray with 2 edges, GN 1/1	PNC 925006	
•	Baking tray for 4 baguettes, GN 1/1 Potato baker GN 1/1 for 28 potatoes	PNC 925007 PNC 925008	
•	Potato baker GN 1/1 for 28 potatoes Non-stick universal pan GN 1/2,	PNC 925008 PNC 925009	
	H=20mm		
	Non-stick universal pan GN 1/2, H=40mm	PNC 925010	_
	Non-stick universal pan GN 1/2, H=60mm	PNC 925011	
•	Compatibility kit for installation on previous base GN 1/1	PNC 930217	


















# SkyLine ProS Electric Combi Oven 6GN1/1





Cold Water inlet 1 CWI2 Cold Water Inlet 2 D Drain

DO Overflow drain pipe



#### **Electric**

Circuit breaker required

400-430 V/3N ph/50-60 Hz Supply voltage:

Electrical power max.: 11.5 kW Electrical power, default: 11.1 kW

Water:

Max inlet water supply

temperature: 30 °C

5 °fH / 2.8 °dH **Hardness** Chlorides: <10 ppm Conductivity: >50 µS/cm Drain "D": 50mm Water inlet "FCW" connection: 3/4" 1-6 bar Pressure, bar min/max:

Electrolux Professional recommends the use of treated water,

based on testing of specific water conditions.

Please refer to user manual for detailed water quality

information.

#### Installation:

Clearance: 5 cm rear and Clearance:

right hand sides.

Suggested clearance for service access: 50 cm left hand side.

Capacity:

GN: 6 - 1/1 Gastronorm

Max load capacity: 30 kg

#### **Key Information:**

Door hinges:

External dimensions, Width: 867 mm External dimensions, Depth: 775 mm Weight: 111.5 kg External dimensions, Height: 808 mm Net weight: 111.5 kg Shipping weight: 128.5 kg Shipping volume: 0.85 m<sup>3</sup>

#### **ISO Certificates**

ISO Standards: 04











